

GV-HOUS-HB



FEATURES

INCLUDES MOUNTING BRACKET

- Extruded Aluminum Construction
- Includes Heater/Blower
- Hinged Cover with lock receptacle
- Easy Access with Front Cover Hinge
- Gasket protected cover
- Accommodates cameras with a maximum size of 9.45(L) x 4.13(W) x 3.15(H) inches.
- IP 66 Rated ensures maximum protection against water, dust, heat and all the elements

SPECIFICATIONS

- Viewing Material: Plate Glass 5mm, 0.2"
- Construction: Extruded Aluminum
- Cable Entry: Gland fitting on bottom of housing
- Latch: Located at rear of housing. Accepts padlock for security
- Camera Mounting: Removable camera sled
- Heater: 24VAC
- Fan: 24VAC
- Weight: 3.52 Kg, 7.76lbs
- Dimensions: (D) 390mm, 15.35" X (W)140mm, 5.51" X (H) 115mm, 4.53"
- Maximum Camera Size (D) 240mm, 9.45" X (W) 105mm, 4.13" X (H) 80mm, 3.15"
- Heater/blower module: 24 Vac, less than 10 VA
- Heater: ON = Less than 57F /OFF = More than 77F
- Maximum current draw: 350 mA
- Average current draw: 250 mA
- Fan: ON = More than 104F /OFF = Less than 86F
- Average current draw: 150 mA

www.abav.ca