

PC-3002 Dome Camera



Specification

Model PC-719D

1/3" Indoor Color Dome Camera

Image Device	1/3" Panasonic D5 Color CCD
Total Picture Elements	NTSC / 537(H) x 505(V) PAL / 537(H) x 597(V)
Effective Picture Elements	NTSC / 510(H) x 492(V) PAL / 500(H) x 582(V)
Scanning System	NTSC / EIA Standard 525 lines, 30 frames/sec PAL / CCIR Standard 625 lines, 25 frames/sec
Synchronizing System	Internal Sync.
Horizontal Resolution	420 TV Lines
Electronic Shutter Control	Auto-Electronic : NTSC / EIA (1/60~1/100000) PAL / CCIR (1/50~1/100000)
Gamma	0.45 / 1
Minimum Illumination	0.5 lux./F2.0
Video Output Level	Composite, 1 Vp-p / 75 ohms
Video S/N Ratio	48dB (AGC OFF)
Water Resistant	N/A
Lens Type	Board Lens 3.6mm, 6mm, 8mm (Optional)
Power-requirement	DC12V
Power Consumption	1.2W (Max)
Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~70°C
Dimensions	107mm (Diameter) x 65mm (H)
Weight	125g