

WC-2503

Specifications subject to change

Wireless, Color Weatherproof IR Camera



Compatible with
WR-2501 & VMW-2.5LCD Receivers

WC-2503

Features

- Wireless transmission - speeds installations & eliminates cable runs.
- IR LEDs - camera can see in the dark.
- 4 channels - multiple cameras can operate in the same area or system.

Specifications

Image Sensor	.1/4" CCD
Resolution	420 lines
Lens	6mm
Total Pixels	512 x 492 (NTSC)
Min. Illumination	0 lux (with IR LED) / 1 lux (without IR LEDs)
Transmission Frequency	ISM 2,400MHz-2,483MHz - 4 channels
Transmission Power	10mW/CE; 2mW/FCC
Modulation Type	FM
Bandwidth	18MHz
Power Supply	Regulated 12V DC power supply included - UL approved
Current Consumption	120mA (IR OFF) / 270mA (IR ON)
Unobstructed Effective Range	300 feet
Night Vision Range	45 feet*
Dimensions	60mm (W) x 90mm (D) x 138mm (H) 2 1/2" (W) x 3 1/2" (D) x 5 1/2" (H)
Weight	10 oz.
Operating Temperature	-14°F to 122°F

- Channel Frequency: CH1=2,414MHz; CH2=2,432MHz; CH3=2,450MHz; CH4= 2,468MHz
- Actual transmission range may vary according to the weather, location, interference and building construction.

* Depending on scene reflection

www.abav.ca